





T10 Label Rewinder

The Rewinder Everyone Can Use

The T10 rewriter has an idler arm that can be positioned to rewind labels from either side of the printer.

Depending on the user's requirements, the rewriter can rewind "inside or outside" label rolls.




Modular core adaptor fits 1", 1.5" & 3" core sizes



Colored LED indicator provides rewriter operation status



Rewinding direction switch to rewind "inside or outside" label rolls



Easy assembly lock module for quickly and firmly label roll holding

Model	T10
Paper width	4.72" (Max.)
Rewind Speed	12 IPS
Label Roll	8" (Max.)
Core Roll	Coreless 1" (25.2 - 25.6 mm) 1.5"x2 (37.4 - 38 mm & 40 - 40.6 mm) 3" (76 - 76.6 mm)
Label Roll Weight	5 Kg
Rewinding	Label Inside / Outside
Switches	Rewind
Motor	Hybrid Motor
Power	100~240V AC 24W, 24V Adapter
Environment	Operating Temp.: 41°F to 104°F(5°C to 40°C) Storage Temp.: -4°F to 122°F(-20°C to 60°C)
Humidity	10-85% (non-condensing RH)
Size (H*W*D)	303 mm * 180 mm * 349 mm
Agency Approvals	CE, FCC Class A
Weight	5 Kg (11 lb)

* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.